

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1-11 and ADD new claims 17-40 in accordance with the following:

1. (CURRENTLY AMENDED) A coordinate detection device, comprising:
 an input unit, having a surface thereof, to which a coordinate value is input by an input ~~means~~ device;
 a calculation unit calculating a ~~difference~~ distance between coordinate values of previous and current input operations by said input unit, the coordinate values being successive over detachment of the input ~~means~~ device from the surface of said input unit; and
 a setting unit setting, in said calculation unit, a coordinate value at a time when the input ~~means~~ device is detached from the surface of said input unit as the coordinate value of the previous input operation.
2. (CURRENTLY AMENDED) The coordinate detection unit device ~~as claimed in~~ according to claim 1, further comprising:
 a determination unit ~~which~~ that determines an operation mode as a relative mode or an absolute mode of said input unit; and
 a control unit ~~which~~ that enables or disables said setting unit based on a determination result of said determination unit.
3. (CURRENTLY AMENDED) The coordinate detection device ~~as claimed in~~ according to claim 2, wherein said determination unit determines the operation mode of said input unit based on a relative contact area formed by a contact of the input ~~means~~ device with the surface of said input unit.
4. (CURRENTLY AMENDED) The coordinate detection device ~~as claimed in~~ according to claim 2, wherein said determination unit determines the operation mode of said input unit based on a time during which the input ~~means~~ device is detached from the surface of

said input unit.

5. (CURRENTLY AMENDED) A method of detecting coordinates, comprising:
inputting a coordinate value to a surface of an input unit, by an input ~~means~~ device;
calculating a ~~difference~~ distance between coordinate values of previous and current input
by said inputting, the coordinate values being successive over detachment of the input ~~means~~
device from the surface of said input unit; and
setting, in said calculating, a coordinate value input at a time when the input ~~means~~
device is detached from the surface of the input unit as the coordinate value of the previous
input operation.

6. (CURRENTLY AMENDED) The method as claimed in claim 5, further
comprising:
determining an operation mode of said inputting as a relative mode or an absolute mode;
and
enabling or disabling said setting based on a determination result of said determining.

7. (CURRENTLY AMENDED) The method as claimed in claim 6, wherein
determining determines the operation mode of said inputting based on a relative contact area
formed by a contact of the input ~~means~~ device with the surface of the input unit.

8. (CURRENTLY AMENDED) The method as claimed in claim 6, wherein said
determining determines the operation mode of said inputting based on a time during which the
input ~~means~~ device is detached from the surface of the input unit.

9. (CURRENTLY AMENDED) A coordinate detection device, comprising:
an input unit, having a surface thereof, to which a coordinate value is input;
a calculation unit calculating a ~~difference~~ distance between a coordinate value of a first
input operation and a coordinate value of a second input operation; and
a setting unit setting, in said calculation unit, the coordinate value of the first input
operation as the final coordinate value input of the first input operation.

10. (CURRENTLY AMENDED) The coordinate detection unit according to claim 9, further comprising:

a determination unit determining an operation mode of said input unit as a relative mode or an absolute mode; and

a control unit enabling or disabling said setting unit based on a determination result of said determination unit.

11. (CURRENTLY AMENDED) The coordinate detection device according to claim 10, wherein said determination unit determines the operation mode of said input unit based on a relative ~~an~~ area of contact area between an input part and the surface of said input unit.

12. (PREVIOUSLY PRESENTED) The coordinate detection device according to claim 10, wherein said determination unit determines the operation mode of said input unit based on a time between the end of the first input operation and the beginning of the second input operation.

13. (CURRENTLY AMENDED) A method of detecting coordinates, comprising:
inputting at least one coordinate value to a surface of an input unit;
setting a coordinate value of a first inputting as the final coordinate value input of the first inputting if a second inputting has not occurred for a predetermined time; and
calculating a ~~difference~~ distance difference between the set coordinate value of the first inputting and an initial coordinate value of the second inputting.

14. (CURRENTLY AMENDED) The method according to claim 13, further comprising:

determining an operation mode of inputting as a relative mode or an absolute mode; and
enabling or disabling said setting based on a result of said determining.

15. (CURRENTLY AMENDED) The method according to claim 14, the determining based on a relative ~~an~~ area of contact of the inputting.

16. (PREVIOUSLY PRESENTED) The method according to claim 14, the determining based on a time between the first inputting and the second inputting.

17. (NEW) A writing device, comprising:
an input unit, having a surface thereof, to which a coordinate value is input by an input device;
a calculation unit calculating a distance between coordinate values of previous and current input operations by said input unit, the coordinate values being successive over detachment of the input device from the surface of the input unit; and
a setting unit setting, in said calculation unit, a coordinate value at a time when the input device is detached from the surface of said input unit as the coordinate value of the previous input operation.
- ✓ 18. (NEW) The writing device according to claim 17, further comprising:
a determination unit determining an operation mode as a relative mode or an absolute mode of the input unit; and
a controller to enable or disable the setter unit based on a determination result of the determination unit.
- Cont³ 19. (NEW) The writing device according to claim 18, wherein the determination unit determines the operation mode of the input unit based on a relative size of a contact area formed by a contact of the input device with the surface of the input unit.
- ✓ 20. (NEW) The writing device according to claim 18, wherein the determination unit determines the operation mode of the input unit based on a time during which the input device is detached from the surface of the input unit.
- ✓ 21. (NEW) A method of detecting coordinates of a writing character, comprising:
inputting a coordinate value of a writing character to a surface of an input unit, by an input device;
calculating a difference in distance between coordinate values of a previous and a current input, the coordinate values being successive over detachment of the input device from the surface of said input unit; and
setting, in the calculating, a coordinate value input at a time when the input device is detached from the surface of the input unit as the coordinate value of the previous input operation.

22. (NEW) The method according to claim 21, further comprising:
 and determining an operation mode of the inputting as a relative mode or an absolute mode;
 enabling or disabling the setting based on the determining.

23. (NEW) The method according to claim 22, wherein the determining determines the operation mode of the inputting based on a relative size of a contact area formed by a contact of the input device with the surface of the input unit.

24. (NEW) The method according to claim 22, wherein the determining determines the operation mode of the inputting based on a time during which the input device is detached from the surface of the input unit.

25. (NEW) A writing device, comprising:
 an input unit, having a surface thereof, to which a coordinate value of a writing character is input;
 a calculator calculating a distance between a coordinate value of a first input operation and a coordinate value of a second input operation; and
 a setting unit setting, in the calculator, the coordinate value of the first input operation as the final coordinate value input of the first input operation.

26. (NEW) The writing device according to claim 25, further comprising:
 a determination unit determining an operation mode of the input unit as a relative mode or an absolute mode; and
 a controller enabling or disabling the setting unit based on a determination result of the determination unit.

27. (NEW) The writing device according to claim 26, wherein the determination unit determines the operation mode of said input unit based on a relative area of contact between an input part and the surface of the input unit.

28. (NEW) The writing device according to claim 26, wherein the determination unit determines the operation mode of said input unit based on a time between an end of the first input operation and a beginning of the second input operation.

29. (NEW) A method of detecting coordinates of a writing character, comprising:
inputting at least one coordinate value of the writing character to a surface of an input unit;
setting a coordinate value of a first inputting as the final coordinate value input of the first inputting if a second inputting has not occurred for a predetermined time; and
calculating a distance between the set coordinate value of the first inputting and an initial coordinate value of the second inputting.

30. (NEW) The method according to claim 29, further comprising:
determining an operation mode of inputting as a relative mode or an absolute mode; and
enabling or disabling the setting based on a result of the determining.

31. (NEW) The method according to claim 29, the determining based on a relative area of the contact of the inputting.

Cont
32. (NEW) The method according to claim 29, the determining based on a time between the first inputting and the second inputting.

33. (NEW) A computer-readable recording medium that stores a method of detecting coordinates comprising:
inputting a coordinate value to a surface of an input unit, by an input device;
calculating a distance between coordinate values of previous and current input by said inputting, the coordinate values being successive over detachment of the input device from the surface of said input unit; and
setting, in said calculating, a coordinate value input at a time when the input device is detached from the surface of the input unit as the coordinate value of the previous input operation.

34. (NEW) The computer-readable recording medium according to claim 33, the method further comprising:
determining an operation mode of the inputting as a relative mode or an absolute mode;
and
enabling or disabling said setting based on a determination result of said determining.

35. (NEW) The computer-readable recording medium according to claim 34, wherein the determining determines the operation mode of said inputting based on a determining of a type of input device by determining a contact area formed by a contact of the input device with the surface of the input unit.

36. (NEW) The computer-readable recording medium according to claim 34, wherein the determining determines the operation mode of said inputting based on a time during which the input device is detached from the surface of the input unit.

37. (NEW) A computer-readable recording medium that stores a method of detecting coordinates comprising:

inputting at least one coordinate value to a surface of an input unit;

setting a coordinate value of a first inputting as the final coordinate value input of the first inputting if a second inputting has not occurred for a predetermined time; and

calculating a distance difference between the set coordinate value of the first inputting and an initial coordinate value of the second inputting.

38. (NEW) The computer-readable recording medium according to claim 37, the method further comprising:

determining an operation mode of inputting as a relative mode or an absolute mode; and enabling or disabling said setting based on a result of said determining.

39. (NEW) The computer-readable recording medium according to claim 38, the determining based on determining of a type of input device by determining an area of contact of the inputting.

40. (NEW) The computer-readable recording medium according to claim 38, the determining based on a time between the first inputting and the second inputting.
